

EN

MetoPrintEasy

Direct thermal printing



Key features

- High quality double-walled clamshell design
- 152,4 mm per second (6") print speed
- 64 MB SDRAM and 128 MB Flash memory
- Easy media loading
- USB 2.0 Highspeed mode and other ports
- Versatile TSPL-EZD firmware emulates Eltron®, Zebra® and Datamax languages out of the box
- 2 years warranty
- ENERGY STAR® qualified
- Operation as stand-alone printer possible

The Meto Print components – printer, templates and labels – are perfectly compatible and supplemented by an extensive retail service concept.

Applications

- Retail
- Point of Sale (POS)
- Identification / Labelling of products
- Stock-taking & inventory control
- Document printing
- Labelling within healthcare application
- Logistics



Technical data

| | |
|--|---|
| Material number | 30000885 |
| Resolution (dpi) | 203 |
| Printing method | Direct Thermal |
| Max. print speed | 152.4 mm/s (6") |
| Max. print width | 108 mm (4.25") |
| Max. print length | 25,400 mm (1000") |
| Enclosure | Double-walled plastic |
| Dimension | 172 mm (W) x 165 mm (H) x 195 mm (D) |
| Weight | 1,5 kg |
| Label roll capacity | 127 mm (5") OD |
| Processor | 32-bit RISC CPU |
| Memory | 128 MB Flash memory / 64 MB SDRAM |
| Interface | RS-232 / USB 2.0 / Ethernet 10/100 Mbps / USB Host |
| RTC (Real-Time-Clock) | Real Time Clock |
| Battery for RTC | CR2032 (3V) Lithium |
| External universal switching power supply | Input: AC 100–240V, 50–60Hz / Output: DC 24V, 2,5A, 60W |
| Operation switch, button, LED | 1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red) |
| Sensors | Transmissive gap sensor / Black mark reflective sensor / Head open sensor |
| Internal fonts | 8 alpha-numeric bitmap fonts / Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font |
| Barcode (1D Barcode) | Code 128 subsets A,B,C, Code128UCC, EAN128, Interleave 2 of 5, Code 39, Code 93, EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS |
| Barcode (2D Barcode) | CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar) |
| Font and barcode rotation | 0°, 90°, 180°, 270° |
| Printer language | TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL) |
| Templates | Maximum one print template may be utilized within printer |
| Media type | Continuous, black mark, fan-fold, notched (outside wound) |
| Media width | 19 ~ 114 mm (0.7" ~ 4.5") |
| Media thickness | 0.055 ~ 0.19 mm (2,16 ~ 7.48 mil) |
| Media core diameter | 25.4 ~ 38 mm (1" ~ 1.5") |
| Label length | 10 ~ 25,450 mm (0.39" ~ 1,000") |
| Limited warranty | Printer: 2 years / Print head: 25 km (1 million inches) or 12 months which comes first / Platen: 50 km (2 million inches) or 12 months which comes first |
| Safety regulation | CE Class B, TÜV / Safety, ENERGY STAR® |
| Environmental concern | Comply with RoHS, WEEE |